















TECHNICAL SPECIFICATION

The Chute Weigh system is ideally suited for conversion of a manual or hydraulic livestock squeeze chute into a working livestock scale. Installation can be portable or permanent depending on specific application.

FEATURES & BENEFITS

Wide range of capacities – 3500 lb (1700 kg) 5,000 lb (2500 kg) or 10,000 lb (5000 kg) gross weighing capacity.

Low profile – Less than 3.50 in (8.89 cm) high.

Heavy-duty construction – Super heavy-duty steel chassis construction.

Easy mounting – Mounting under manual or hydraulic livestock squeeze chutes.

Weigh Bar cables – Tough polyurethane weigh bar cables.

Weatherproof construction – Aerospace-developed sealing agent provides ultimate protection against moisture and ensures long term durability in harsh agricultural environment.

Herd management – Weight indicator is compatible with various herd management EID software packages.

Bluetooth – Connect to PC with optional RM-110.

INDICATOR OPTIONS

Choose from the following Avery Weigh-Tronix indicators:

640 Series Indicators – Simple yet accurate and reliable livestock weighing with Auto-LOC and accumulation functions. Choose from the 640, 640M or 640XL.

640M – Features compact design and 1.1 inch (27.94 mm) digital display. Optional rechargeable Lithium-ion battery available providing ultimate site weighing application flexibility.









640/640XL – Rugged and easy to use, the 640 and 640XL are ideal for livestock weighing. Choose the 640 with a 1.1 inch (27.94 mm) display or the 640XL with a 2 inch (50.80 mm) display.

Chute Weigh Livestock Floor Scale

SPECIFICATIONS

Capacity:

CW-10: 10,000 lb (4536 kg) per set. 5000 lb (2268 kg) each Weigh Bar.

CW-5: 5000 lb (2268 kg) capacity per set. 2500 lb (1134 kg) each Weigh Bar.

CW-3.5: 3500 lb (1588 kg) capacity per set.

1750 lb (794 kg) each Weigh Bar. Material: Alloy Steel Weigh Bars

Finish: Gray baked-on powder paint

Accuracy: $\pm 0.25\%$

System Output: 0.38 mV/V @ 5,000 lb (2268 kg) for each

system of 2 Weigh Bars.

Input Resistance: 350 ohms ± 20 ohms

Zero Balance: $\pm 0.5 \text{ mV/V}$

Power Options:

1. Power cable: 12 VDC power cable for external battery. 2. Internal rechargable Lithium-Ion Battery (640M only)

3. Transformer: 115VAC wall mount transformer.

5 Pin Connector Color Code:



Green... +Excitation Black... -Excitation С White... +Signal Red... -Signal Orange... Shield

Cable Length: 20 ft (610 cm) with standard Avery Weigh-Tronix 5-pin cable

Shipping Weight:


CW-3.5: 24 lb (11 kg) for each Weigh Bar unit CW-5: 32 lb (14.5 kg) for each Weigh Bar unit CW-10: 61 lb (28 kg) for each Weigh Bar unit


Warranty: Three years

Dimensions*:

| | CW-10 | | CW-5 | | CW-3.5 | |
|---|-------|--------|-------|-------|--------|-------|
| | in | cm | in | cm | in | cm |
| Α | 44.00 | 111.76 | 32.75 | 83.19 | 24.00 | 60.96 |
| В | 1.38 | 3.50 | 1.06 | 2.69 | 1.06 | 2.69 |
| C | 2.38 | 6.05 | 2.06 | 5.23 | 2.06 | 5.23 |
| D | 0.97 | 2.46 | 0.80 | 2.03 | 0.80 | 2.03 |
| E | 3.44 | 8.73 | 2.87 | 7.29 | 2.87 | 7.29 |
| F | 5.00 | 12.70 | 4.25 | 10.79 | 4.25 | 10.79 |
| G | 41.25 | 104.77 | 24.25 | 61.59 | 16.25 | 41.27 |
| Н | 43.00 | 109.22 | 26.00 | 66.04 | 18.00 | 45.72 |
| 1 | 44.75 | 113.66 | 27.75 | 70.48 | 19.75 | 50.16 |

^{*}Dimensions are listed for one Weigh Bar unit. A system requires two Weigh Bars.







AVERY WEIGH-TRONIX - USA

1000 Armstrong Drive, Fairmont, MN 56031-1439 USA

Toll-Free: (800) 533-0456 Phone: (507) 238-4461 Email: ag@awtxglobal.com www.agscales.com

AVERY WEIGH-TRONIX - UK

Foundry Lane, Smethwick, West Midlands B66 2LP UK

Phone: +44 (0) 845 307 0321 Fax: +44 (0) 121 224 8183 Email: info@awtxglobal.com

www.agscales.com



